





Optimized grease duct enclosure system

- Butt joints, all seams, both layers staggered seam across duct no 3" overlaps
- Contractor friendly transverse butt joint location
- Maximum 3" thickness along all surfaces of the duct
- UL listed for rectangular and round ducts
- UL listed, liquid tight, single layer FastDoor XL for duct access

world leading products - engineered solutions







Thermal Ceramics' Pyroscat XL versus the nearest competitors			
	Thermal Ceramics	Competitor I	Competitor 2
Space requirement	3" per side	3" per side	6" per side
Blanket length (rolled out)	Unrolls to 25 feet minimum	Unrolls to 23 to 25 feet	Unrolls to 23 to 25 feet
Weight	0.75 lbs./sq.ft.	0.75 lbs./sq.ft.	0.90 lbs./sq.ft.
R-Value	4.8 per inch	4.8 per inch	4.2 per inch
Layer I Joint type	Compression at all joints	Compression at all joints	Compression at all joints
Location of Layer I Longitudinal Joint	Anywhere; Contractor's choice	Longitudinal joint must be located at a top corner	Anywhere; Contractor's choice
Layer 2 Joint type	Compression at all joints	Compression at all joints	3" overlap at all joints
Location of Layer 2 Longitudinal Joint	Offset longitudinal seams minimum 6"	Longitudinal joint must be located at a different top corner	Offset outer layer longitudinal joints a minimum 10.5"
System Installation			

For all enquiries, please contact our specialist sales:

Europe

Morgan Advanced Materials Thermal Ceramics T +44 (0) | 5 | 334 4030 europesales@morganplc.com

North America

Morgan Advanced Materials Thermal Ceramics T + I (706) 796 4200 nasales@morganplc.com

South America

Morgan Advanced Materials Thermal Ceramics T +55 (11) 4075 0400 sasales@morganplc.com

Asia

Morgan Advanced Materials Thermal Ceramics T +65 6595 0000 asiasales@morganplc.com

Thermal Ceramics is a business of Morgan Advanced Materials Quadrant, 55-57 High Street, Windsor, Berkshire, SL4 ILP. United Kingdom www.morganthermalceramics.com www.morganadvancedmaterials.com